

# **MICHELIN® X® TWEEL® UTV**

## **AIRLESS RADIAL TIRE**



## **DESIGNED FOR USE ON MILITARY UTVS, ATVS AND SIMILAR EQUIPMENT**

MICHELIN® X® TWEEL® UTV airless radial tires were developed to improve mobility in hazardous environments and conditions where vehicles are exposed to rugged roads, jagged terrain, shock and fragmentation threats from adjacent explosions, and even roadside Improvised Explosive Devices. In the face of these obstacles and direct battle damage, the TWEEL® UTV tire is designed to perform like a pneumatic radial tire, but with the robustness and damage tolerance of an airless tire.

A MICHELIN® X® TWEEL® UTV tire is a single unit that replaces the current pneumatic tire/wheel/valve assembly. Once bolted on, there is no air pressure to maintain, thus eliminating the need to carry spare tires, tools, or repair kits while operating far from base. The full width polyresin spokes help dampen the ride for enhanced operator comfort, while providing outstanding lateral stiffness for excellent cornering and side-hill stability.

[tweel.michelinman.com](http://tweel.michelinman.com)  
[business.michelinman.com](http://business.michelinman.com)

DISTRIBUTION A. Approved for Public Release; Distribution Unlimited. OPSEC #5984





# MICHELIN® X® TWEEL® UTV

## AIRLESS RADIAL TIRE

Deep, open and aggressive tread design cleans mud while providing excellent stability and traction.

Michelin's proprietary Comp10 Cable™ forms a semi-rigid "shear beam", and allows the load to hang from the top.



Zero degree belts and proprietary design provide great lateral stiffness, while resisting damage and absorbing impacts.

Heavy gauge steel hub fits a variety of popular UTV/ATV machines.

High strength, polyresin spokes carry the load and absorb impacts, help dampen the ride, and provide a unique energy transfer that reduces pneumatic bounce.

### HUB DESIGNS



MSPN 68495, 67693, 65492, 64998, 03488 & 54523



MSPN 75085 & 82599



MSPN 21709 & 29242



MSPN 49265 & 10545

**AVAILABLE IN SIZES TO FIT A WIDE RANGE OF MACHINES. FOR MORE DETAILS PLEASE REFER TO THE ONLINE FITMENT GUIDE AT [TWEEL.MICHELINMAN.COM](http://TWEEL.MICHELINMAN.COM)**

MSPN	CAI	Description	Common Fitments	Size	Max Load	Max Speed	Bolt Pattern	True Offset	Industry Offset/ Backspace	Center Hole Dia.	Bolt Hole Dia.	Weight
<b>26X9N 14 SIZE</b>												
68495	316179	X TWEEL ATV	Honda ATV	26x9N14	506 lbs 230 kg	50 mph 80 kph	4x110 mm	+45 mm	5+2	2.7 in 68.5 mm	13 mm	50 lbs. 22.7 kg
67693	698296	X TWEEL UTV	Honda, Kubota RTV	26x9N14 69J	715 lbs 325 kg	62 mph 100 kph	4x110 mm	+52 mm	6+1	2.7 in 68.5 mm	13 mm	57 lbs. 25.7 kg
65492	396708	X TWEEL UTV	Artic Cat, Textron, CAT CUV	26x9N14 69J	715 lbs 325 kg	62 mph 100 kph	4x115 mm	+52 mm	6+1	2.7 in 68.5 mm	13 mm	57 lbs. 25.7 kg
75085	278044	X TWEEL UTV	Most Polaris, Kawasaki Mule Pro 800	26x9N14 69J	715 lbs 325 kg	62 mph 100 kph	4x156 mm	+30 mm	4+3	5.2 in 132 mm	13 mm	50 lbs. 22.7 kg
21709	421944	X TWEEL UTV	Most Can Am; Kawasaki Teryx, Mule 4010; John Deere XUV 590; Yamaha, Arctic Cat, others	26x9N14 69J	715 lbs 325 kg	62 mph 100 kph	4x137 mm	+48 mm	5+2	4.4 in 112 mm	14.3 mm	50 lbs. 22.7 kg
49265	593299	X TWEEL UTV	John Deere XUV 835 and others; ARGO, General Dynamics	26x9N14 69J	715 lbs 325 kg	62 mph 100 kph	5x4.5"	+25 mm	4+3	3.13 in 79.5 mm	13 mm	50 lbs. 22.7 kg
<b>26X11N 14 SIZE</b>												
64998	199685	X TWEEL UTV	Honda, Kubota RTV	26x11N14	1323 lbs 600 kg	62 mph 100 kph	4x110 mm	+35 mm	6+4	2.7 in 68.5 mm	13 mm	79 lbs. 35.8 kg
03488	417016	X TWEEL UTV	Artic Cat, Textron, CAT CUV	26x11N14	1323 lbs 600 kg	62 mph 100 kph	4x115 mm	+35 mm	6+4	2.7 in 68.5 mm	13 mm	79 lbs. 35.8 kg
82599	842835	X TWEEL UTV	Most Polaris, Kawasaki Mule Pro 800	26x11N14	1323 lbs 600 kg	62 mph 100 kph	4x156 mm	+42 mm	7+3	5.2 in 132 mm	13 mm	79 lbs. 35.8 kg
29242	094026	X TWEEL UTV	Most Can Am; Kawasaki Teryx, Mule 4010; John Deere XUV 590; Yamaha, Arctic Cat, others	26x11N14	1323 lbs 600 kg	62 mph 100 kph	4x137 mm	+35 mm	6+4	4.4 in 112 mm	14.3 mm	79 lbs. 35.8 kg
10545	812358	X TWEEL UTV	John Deere XUV 835 and others; ARGO, General Dynamics	26x11N14	1323 lbs 600 kg	62 mph 100 kph	5x4.5"	+40 mm	7+3	3.13 in 79.5 mm	13 mm	79 lbs. 35.8 kg
<b>32X10N 15 SIZE</b>												
54523	485503	X TWEEL UTV AT 2	Polaris MRZR Alpha LTATV	32x10 N15	1543 lbs 700 kg	62 mph 100 kph	5x4.5"	+61.5 mm	7+2	2.9 in 74 mm	16 mm	109 lbs. 49.7 kg

Note: All UTV/ATVs use 60° / Conical / Tapered Lug Nuts. | Product measurements are subject to change and are listed here for your convenience. Please see your MICHELIN representative for up-to-date data.

[tweel.michelinman.com](http://tweel.michelinman.com)  
[business.michelinman.com](http://business.michelinman.com)

Michelin North America Inc., One Parkway South, Greenville, SC 29615  
Michelin North America (Canada) Inc., 2500 Daniel Johnson Blvd., Suite 500, Laval (QC) H7T 2P6  
Copyright © 2021 Michelin North America, Inc. All rights reserved. The Michelin Man is a registered trademark owned by Michelin. | © 2021 MNA(Q). All rights reserved.  
An Equal Opportunity Employer | (BWA 11/21)

DISTRIBUTION A. Approved for Public Release; Distribution Unlimited. OPSEC #5984

